

3 basic things one must know to pick the right air compressor.

1. Amount of air required (LPM)
2. Working pressure required (Min & Max)
3. Kind of air quality required (oil free/moisture Free)



How to ensure good performance from the air compressor/Conditions for Warranty

- Please Supply Non fluctuating Power supply in the range of 210-240(V)
- Check oil window from time to time and ensure the recommended oil level is maintained.
- Place your compressor on a flat surface.
- Do not change factory settings.
- Do not use your air compressor without suction filter and clean it from time to time.
- Change the oil after 200-300 hours of running.
- Place the compressor away from dusty atmosphere/place where painting job is being carried out, the area should be well ventilated.
- Do not let water accumulate in the air reservoir.

Taruu Direct Drive Portable Air Compressor (Professional Grade)

- Heavier construction
- Built in overload motor protection
- Clutch motor with double condenser
- Quality after sales service
- Certified tank quality and size
- 1 Year Warranty*



TECHNICAL SPECIFICATION :

Model No.	TR-0301/10
Motor	2 HP, Single Phase
RPM	2800
Operating Voltage	210-240 volts
Max. Pressure	8 Bar
Free Air Delivery	120 LPM/4.2 CFM @ 90 PSI
Piston Displacement	170 LPM
Tank Volume	10 Litres
Operation	Auto On/Off
Duty Cycle	60%
Approx. Net Weight	19 Kgs
Dimensions (with Cardboard packing)	54*24*51 Cms
Pump	Oil Lubricated

- For Pneumatic tools requiring cfm 4.2 and less.
- Also suitable for Spray Painting, dusting/cleaning, tyre inflation, Pressure Testing

Taruu Direct Drive Portable Air Compressor (Professional Grade)

- Heavier construction
- Built in overload motor protection
- Clutch motor with double condenser
- Certified tank quality and size
- 1 Year Warranty*



TECHNICAL SPECIFICATION :

Model No.	TR-0302/30
Motor	2.5 HP, Single Phase
RPM	2800
Operating Voltage	210-240 volts
Max. Pressure	8 Bar
Free Air Delivery	150 LPM/5.3 CFM @ 90 PSI
Piston Displacement	220 LPM
Tank Volume	30 Litres
Operation	Auto On/Off
Duty Cycle	60%
Dimensions (with Cardboard packing)	68*32*66 Cms
Pump	Oil Lubricated

- For Pneumatic tools requiring cfm 5.3 and less.
- Also suitable for Spray Painting, dusting/cleaning, tyre inflation, Pressure Testing