

## **3** basic things one must know to pick the right air compressor.

1. Amount of air required (LPM)
2. Working pressure required (Min & Max)
3. Kind of air quality required (oil free/moisture Free)



## **How to ensure good performance from the air compressor/Conditions for Warranty**

- Please Supply Non fluctuating Power supply in the range of 210-240(V)
- Check oil window from time to time and ensure the recommended oil level is maintained.
- Place your compressor on a flat surface.
- Do not change factory settings.
- Do not use your air compressor without suction filter and clean it from time to time.
- Change the oil after 200-300 hours of running.
- Place the compressor away from dusty atmosphere/place where painting job is being carried out, the area should be well ventilated.
- Do not let water accumulate in the air reservoir.

## Taruu Low Noise & Oil Free Air Compressor (Professional Grade)

- 1 Year Warranty\*
- For Intermittent duty
- Improved Motor
- Built in overload motor protection
- Heavier construction
- Silent operation
- Certified tank quality and size



### TECHNICAL SPECIFICATION :

Model No.	TR-2X750/50
Motor	2 HP (750 W x2), Single Phase
Operating Voltage	210-240 volts
Max. Pressure	8 Bar
Free Air Delivery	120 LPM/4.2 CFM @ 90 PSI
Piston Displacement	170 LPM
Tank Volume	50 Litres
Operation	Auto On/Off
Duty Cycle	30%
Dimensions (with Cardboard packing)	65*31*61 Cms
Pump	No Lubricated Required

- For Pneumatic tools requiring cfm 4.2 and less.
- Also suitable for dusting/cleaning, tyre inflation, Pressure Testing

## Taruu Low Noise & Oil Free Air Compressor (Professional Grade)

- For Intermittent duty
- Silent operation
- 1 Year Warranty\*



### TECHNICAL SPECIFICATION :

Model No.	TR-1500x2/120
Motor	2 HP (1550 W x2)
Operating Voltage	210-240 volts
Max. Pressure	8 Bar
Free Air Delivery	240 LPM/8.4 CFM @ 90 PSI
Piston Displacement	340 LPM
Tank Volume	120 Litres
Operation	Auto On/Off
Duty Cycle	30%
Pump	No Lubricated Required

- For Pneumatic tools requiring cfm 8.4 and less.
- Also suitable for dusting/cleaning, tyre inflation, Pressure Testing